

Socket outlets without earthing contact

- for 4-hole screw fitting

Dutch socket outlets



Socket outlet without earth contact NETHERLANDS

▶ 210

- enhanced contact protection
- screw terminals

- 2pole



Rated voltage 250 V~
Rated current 16 A
Mirror depth 14.5 mm

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 182 .. 63
9 188 .. 63
9 191 .. 63
9 1933 64

Page

Connection terminals according to IEC 60884-1
Enhanced contact protection (child protection) according to IEC 60884-1

Design	Order no.	PU
anthracite matt	9 6194 25 05	10
grey matt	9 6194 25 06	10
polar white matt	9 6194 25 02	10
black matt	9 6194 05	10



Euro-American Standard socket outlets



Socket outlet without earthing contact EURO-AMERICAN STANDARD

▶ 210

- enhanced contact protection
- screw terminals

- 2pole



Rated voltage 250 V~
Rated current 10 A

Suitable for

Contact protection box Ø 45 mm
Contact protection box Ø 49 mm
Contact protection box 2gang
Contact protection box 3gang

Order no.

9 1820 .. 63
9 188 .. 63
9 191 .. 63
9 1933 64

Page

Not suitable for SCHUKO plug according to DIN 49441.
Standard GB 1002

Connection terminals according to IEC 60884-1
Enhanced contact protection (child protection) according to IEC 60884-1

Design	Order no.	PU
anthracite matt	8 6257 25 05	200
polar white matt	8 6257 25 02	200
brown matt	9 6257 25 01	10
anthracite matt	9 6257 25 05	10
grey matt	9 6257 25 06	10
polar white matt	9 6257 25 02	10
black matt	9 6257 25 03	10

