


Non-insulated Silver Brazed Terminals

from 0.25 to 70 mm²



General features

✓ Material: tin-plated electrolytic copper.



mm²
Rigid / Flexible



Ø mm

W

F

Ø i



mm ² Rigid / Flexible	Item code	Part No.	Packing	Stud size Ø mm	W	F	Ø i	Type of dies
0.25 / 1.5	7380000	MB1,5-3	100	3	5.5	9.8	1.7	Tool MB524
	7380001	MB1,5-4	100	4	8	11.8	1.7	
	7380002	MB1,5-5	100	5	8	11.8	1.7	
	7380003	MB1,5-6	100	6	11.6	15.8	1.7	
	7380004	MB1,5-8	100	8	11.6	15.8	1.7	
1 / 2.5	7380005	MB2,5-3	100	3	6.6	9.6	2.3	Tool MB524
	7380006	MB2,5-4	100	4	8.5	12.6	2.3	
	7380021	MB2,5-5 S	100	5	8.5	12.6	2.3	
	7380007	MB2,5-5	100	5	9.5	12.1	2.3	
	7380008	MB2,5-6	100	6	12	15.8	2.3	
4 / 6	7380009	MB2,5-8	100	8	12	15.8	2.3	..MUJ6-8
	7380028	MB6-3,5	100	3,5	7.2	12.1	3.4	
	7380014	MB6-4	100	4	9.5	15.1	3.4	
	7380015	MB6-5	100	5	9.5	15.1	3.4	
	7380016	MB6-6	100	6	12	19	3.4	
6 / 10	7380017	MB6-8	100	8	15	19.5	3.4	..MUJ6-8
	7380018	MB6-10	100	10	15	19.5	3.4	
	7380012	MB8-4	100	4	12	17.8	4.5	
	7380011	MB8-5	100	5	12	17.8	4.5	
	7380010	MB8-6	100	6	12	17.8	4.5	
10 / 16	7380020	MB8-8	100	8	15	22.3	4.5	..MUJ6-8
	7380030	MB8-10	100	10	15	22.3	4.5	
	7380035	MB8-12	100	12	20	23.5	4.5	
	7380041	MB14-5	100	5	12	23.8	5.8	
	7380040	MB14-6	100	6	12	23.8	5.8	
25-35 / 16-26	7380050	MB14-8	100	8	16	24.7	5.8	..MUJ14...
	7380060	MB14-10	100	10	16	24.7	5.8	
	7380070	MB14-12	100	12	22	30.3	5.8	
	7380080	MB22-6	50	6	16.5	25.5	7.7	
	7380090	MB22-8	50	8	16.5	25.5	7.7	
50 / 26-42	7380100	MB22-10	50	10	16.5	25.5	7.7	..MUJ22...
	7380110	MB22-12	50	12	22	31.7	7.7	
	7380131	MB38-6	50	6	15.3	31.4	9.4	
	7380130	MB38-8 S	50	8	15.3	31.4	9.4	
	7380125	MB38-8	50	8	22	31.7	9.4	
70 / 42-60	7380140	MB38-10 S	50	10	15.3	31.4	9.4	..MUJ38...
	7380148	MB38-10	50	10	22	31.7	9.4	
	7380150	MB38-12	50	12	22	31.7	9.4	
	7380169	MB60-6	50	6	22	38.7	11.4	
	7380170	MB60-8	50	8	22	38.7	11.4	
70 / 42-60	7380180	MB60-10	50	10	22	38.7	11.4	..MUJ60...
	7380190	MB60-12	50	12	22	38.7	11.4	
	7380200	MB60-14	50	14	32	41.5	11.4	
	7380201	MB60-16	50	16	32	41.5	11.4	



Nominal section (mm²)



Packing



Stud size



Type of dies


Unless otherwise stated, all dimensions are in millimeters.

Non-insulated Silver Brazed Terminals

from 95 to 185 mm²

General features

✓ Material: tin-plated electrolytic copper.



mm²

Rigid / Flexible



Item code



Part No.



Ø mm

W

F

Ø i



	Item code	Part No.		Ø mm	W	F	Ø i	
95 / 60-78	7380210	MB70-8	50	8	24	38	13.3	..MUJ70...
	7380220	MB70-10	50	10	24	38	13.3	
	7380230	MB70-12	50	12	24	38	13.3	
	7380240	MB70-14	50	14	32	44	13.3	
	7380241	MB70-16	50	16	32	44	13.3	
120 / 78-96	7380250	MB80-8	25	8	27	40.7	14.5	..MUJ80...
	7380260	MB80-10	25	10	27	40.7	14.5	
	7380270	MB80-12	25	12	27	40.7	14.5	
	7380280	MB80-14	25	14	32	52	14.5	
	7380285	MB80-16	25	16	32	52	14.5	
150 / 96-120	7380290	MB100-10	25	10	28.5	41.4	16.4	..MUJ100...
	7380300	MB100-12	25	12	28.5	41.4	16.4	
	7380310	MB100-14	25	14	32	52	16.4	
	7380320	MB100-16	25	16	32	52	16.4	
	7380325	MB100-18	25	18	32	52	16.4	
185 / 117-150	7380330	MB100-20	25	20	32	52	16.4	..MUJ150
	7380340	MB150-10	10	10	36	50	19.5	
	7380350	MB150-12	10	12	36	50	19.5	
	7380360	MB150-14	10	14	36	50	19.5	
	7380370	MB150-16	10	16	36	50	19.5	
	7380375	MB150-18	10	18	36	63	19.5	
	7380380	MB150-20	10	20	36	63	19.5	



Nominal section (mm²)



Packing



Stud size



Type of dies

Unless otherwise stated, all dimensions are in millimeters.